

CHAMELEON® 1X2 FLY TRAP

Comprehensive unit specification

Part No.	CHA1X2004 (014) / CHA1X2104 (114)
Description	Chameleon® 1 x 2 White / Stainless Steel
Unit Class	I
Guarantee	3 years
Area of Coverage	90 m ²
Voltage Range	220-240V
Frequency Range	50-60Hz
IP Rating	20
Ambient operating temperatures	0 to +40°C *
Power Consumption	45W
Glueboard (Quantity/Reference)	1 / BOACHA850
Tube (Quantity/Reference/Description)	2 / TUB15W490 / 15 Watt 45cm long T8 Quantum® shatterproof
Mains Cable	IEC / HO5RN-F
Unit Dimensions mm	H315 x W485 x D65
Carton Dimensions	H370 x W540 x D120
Unit Weight	4,3 kg
Carton Weight	4,6 kg

* recommended operating temperature range, should they be exceeded in either way it may affect the working of the unit.

The Chameleon® 1x2 is compliant with the essential requirements of the EMC Directive 2014/30/EU and the Low Voltage Directive 2006/95/EC. The unit is CE marked.

Additionally, the Chameleon® 1x2 unit is compliant with the following International Standards:

EN 55014-1:2001	Electromagnetic compatibility. Requirements for household appliances, electric tools and similar apparatus. Emission.
EN 61000-3-2:2001	Electromagnetic compatibility (EMC) -- Part 3-2: Limits – Limits for harmonic current emissions.
EN 61000-3-3:1995	Electromagnetic compatibility (EMC) – Limits. Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems.
IEC 60335-1:2010	Safety of household and similar electrical appliances – Part 1: General requirements.
IEC 60335-2-59:2002	Household and similar electrical appliances – Safety – Part 2-59: Particular requirements for insect killers.

Engineering and Technical Manager Signature:



Dated: 25th April 2018