

CHAMELEON® 2X2 FLY TRAP

Comprehensive unit specification

Part No.	CHA2X2004 (014) / CHA2X2104 (114)
Description	Chameleon® 2 x 2 White / Stainless Steel
Unit Class	I
Guarantee	3 years
Area of Coverage	180 m ²
Voltage Range	220-240V
Frequency Range	50-60Hz
IP Rating	20
Ambient operating temperatures	0 to +40°C *
Power Consumption	80W
Glueboard (Quantity/Reference)	2 / BOACHA850
Tube (Quantity/Reference/Description)	4 / TUB15W490 / 15 Watt 45cm long T8 Quantum® shatterproof
Mains Cable	IEC / HO5RN-F
Unit Dimensions mm	H315 x W485 x D125
Carton Dimensions	H385 x W575 x D185
Unit Weight	6 kg
Carton Weight	7 kg

* recommended operating temperature range, should they be exceeded in either way it may affect the working of the unit.

The Chameleon® 2x2 is compliant with the essential requirements of the EMC Directive 2014/30/EU and the Low Voltage Directive 2006/95/EC. The unit is CE marked.

Additionally, the Chameleon® 2x2 unit is compliant with the following International Standards:

- EN 55014-1:2001 Electromagnetic compatibility. Requirements for household appliances, electric tools and similar apparatus. Emission.
- EN 61000-3-2:2001 Electromagnetic compatibility (EMC) - Part 3-2: Limits – Limits for harmonic current emissions.
- EN 61000-3-3:1995 Electromagnetic compatibility (EMC) - Part 3: Limits - Section 3: Limitation of voltage fluctuations and flicker in low-voltage supply systems for equipment with rated current ≤ 16 A
- IEC 60335-1:2010 Safety of household and similar electrical appliances – Part 1: General requirements.
- IEC 60335-2-59:2002 Household and similar electrical appliances – Safety – Part 2-59: Particular requirements for insect killers.

Engineering and Technical Manager Signature:



Dated: 25th April 2018